

TCP-Ax - RUGGED TIME CODE PROCESSORS - FLIGHT QUALIFIED



GPS / HaveQuick / IRIG-B / PTP Referenced

Time Code Processors with Programmable

HaveQuick / 1 PPS / IRIG-B and Video Insertion Output Capability



AS9100D Certificate Number : C0210021-AS3



TCP-Ax - RUGGED TIME CODE PROCESSORS - FLIGHT QUALIFIED

Product Overview

The TCP-Ax range of advanced rugged Time Code Processors are extremely accurate and robust instruments that are easily configured with a PC via USB to synchronize with a wide variety of external time sources, including GPS, IRIG-B, Have Quick, and PTP (IEEE 1588).



Two size variants are offered, the TCP-AS (Standard - Top Right) and the TCP-AM (Miniature version - Bottom Right). The TCP-AS provides additional connectivity, an option for Lithium Ion cell backup and options to facilitate video insertion (PAL and NTSC).

Ethernet options are provided with a built in SNTP web-server that provides a secure user friendly interface for configuring the unit and I/O functionality along with PTP & NTP functions. GPS options also provide an RS232 interface port with NMEA message output.

Each unit provides an IRIG-B (121-127) output along with five configurable and programmable digital output signal generators for 1PPS, GPS Have Quick, IRIG-DC, GPS Lock. In addition, four digital event capture inputs are provided that are accurate to within 100ns, making the TCP-Ax the ideal instrument for on board data capture, UTC referenced time stamping and timecode signal distribution.



All units are flight qualified and tested to MIL-STD 810F and 461E, CE102 and RE 102.

Key Feature Summary

Timing & Interfaces
<ul style="list-style-type: none"> • Time reference inputs - 16 Channel GPS, IRIG-B, Have Quick, PTP (IEEE 1588) Slave • Simple setup using PC via USB port • +/-12 hour time offset programmability with 1 second resolution • Galileo capable option, with firmware change • 4 User Selectable Event Capture Input accurate to 100ns • Ethernet 10/100BaseT option : PTP (IEEE-1588) Master / Slave options + NTP Network Interface • High stability disciplined hybrid OC/TCXO as standard • Internal clock backup via SuperCap as standard - Option for high capacity Li-Ion backup • Rugged compact design - meets MILSTD 810F / 461E, CE102 & RE 102 • Video Signal Time Stamp Insertion Option (TCP-AS) • 9 - 36V DC Input - 1.5 watts consumption
Input Options
<ul style="list-style-type: none"> • 16 Channel GPS via active antenna • Ethernet 10/100BaseT PTP (hardware support) Slave Mode • Have Quick • 4 channel event capture • IRIG-B
Output Options
<ul style="list-style-type: none"> • IRIG-B + 5 programmable outputs as 1PPS, IRIG-B, HaveQuick • Ethernet 10/100BaseT PTP (hardware support) Master Mode or NTP Server • RS232 NMEA Messages (Time & Location) with GPS option

TCP-Ax - RUGGED TIME CODE PROCESSORS - FLIGHT QUALIFIED

Specifications



Specifications - TCP-Ax	
Input Sync Options	Details
Std : IRIG-B	Accuracy within +/- 10 μ s of external source at initial synchronization
Std : GPS-HQII	Accuracy within +/- 200 ns of external source
Optional : GPS	16 Channel GPS Receiver Option - Galileo option available
Optional : PTP (IEEE-1588)	Slave option from PTP source - <i>See Network Interface Options below</i>
Inputs - Event Capture	
Std : Four Programmable Inputs	Event 1 to Event 4, De-bounced switch closure input, Logic level input (accuracy +/- 100 ns)
Outputs	
Std : IRIG Outputs	IRIG-B121...127 via BNC : 3.0 Vp-p (no load), 2.0 Vp-p (into 600 ohms)
Std : Five Programmable Outputs	Programmable Pulses 1 to 4, 1PPS, GPS On Time Mark, GPS Have Quick II, GPS Lock, IRIG-DC
Optional : IRIG Output Options	IRIG-A, IRIG-E, IRIG-H
Optional : NTP	NTP Server Master Clock from GPS reference option - <i>See Network Interface Options below</i>
Optional : PTP (IEEE-1588)	PTP Master Clock Mode from GPS reference option - <i>See Network Interface Options below</i>
Optional : RS-232 (with GPS)	NMEA messages (Time/Location) with GPS option Connector : Glenair - Pt No 801-011-07M7-10SA Mates with: Glenair Pt No: 801-008-16M7-10PA
Internal Time Base Accuracy	
Stability	1 ppm (@ 25 deg C)
Stability over temperature	1 ppm (-40 to +40 deg C)
Long Term Stability	1 ppm (1 year @ 25 deg C)
Calibration Range	+/- 8 ppm
Calibration Accuracy	+/- 15 ppb of external time source (@ 25 deg C) when disciplined
Time Offset	Programmable + / - 12 Hours - 1 second resolution
Network Interface Options	
Standard Physical Option	1 port : 10/100 Base T via RJ45 connector
Protocols	NTP Version 3 [RFC 1305] , SNTP compatible (RFC 2030) SNMP, IEEE802.3, UDP/IP, ICMP
Optional : Network Interfaces	4 options available : NTP Time Server, NTP Client, PTP Grandmaster, PTP Slave
Status LEDs	Power, IRIG-B, GPS status
Environmental	
Temperature	Operating : -40°C + 60°C Storage : -50°C + 70°C - (Non Li-Ion option)
Humidity	95 % non condensing
Power	9 - 36 V DC 1.5 Watts Connector : Glenair - Pt No 801-011-07M5-5SA Mates with: Glenair Pt No: 801-008-16M5-5PA
Physical	TCP-AS - 15.0 cm x 10.8 cm x 5.9 cm (5.9" x 4.3" x 2.3") Weight : 0.7 to 1.4 kg (1.5 to 3 lb) depending upon options TCP-AM - 14.9 cm x 10.3 cm x 3.7 cm (5.9" x 4.0" x 1.5") Weight : 0.5 kg (1 lb)
Compliance	Tested to MIL-STD 810F and 461E CE102 and RE 102
Options for TCP-AS only	TCP-AS only (Larger Variant)
Optional : Time Display	Optional time of day display LCD
Optional : Ruggedised 10/100BaseT Network Port	Optional Ruggedised 10/100BaseT Interface
Optional Clock Backup	Option 1 : Super Cap option (See temperature specs) Option 2 : Lithium Ion Battery Pack
Optional : Video Insertion	Features : PAL and NTSC video Input / Output - Auto detect video signal Programmable overlay position and content - Event markers (from event inputs) Options for 2 channels (front) + option for additional 2 channels (rear)

Satisfied customers include..

ABB Singapore

Airbus Defence & Space

ASM Technologies Ltd

Atkins

Babcock International

BAE Systems

BBC

Carillion Rail

CMC Engineering Malaysia

EDF Energy

Finmeccanica, UK

Indian Navy

Jakarta Metro

Leonardo Electronics Defence And Security

London Stock Exchange

London Underground

MBDA Ltd

MTRC Hong Kong

National Air Traffic Services

NEC

Network Rail National

Northrop Grumman Park Air Systems Ltd

Qinetiq Ltd

Raytheon Systems Ltd

Rockwell Automation

SBS Transit Singapore

Siemens Rail

Siemens Rail Automation Holdings Ltd.

Singapore Stock Exchange

St Electronics Singapore

Telent Technology Services Limited

Teligent

Thales UK

Transport For London

Viacom



Asia, China, India, Japan

Mr Neil Pitman
Director of Sales - Asia
China, India, Japan

+44 (0) 1376 5141 14 Phone
neil.pitman@timefreq.com

Europe, Middle East, Africa, Australia

Mr David Wright
Director of Sales, Europe, Middle East,
Africa, Australia

Tel : +44 (0) 1694 722891
dwright@timefreq.com

United Kingdom

Mr Mark Aheme
Director of Sales, UK

Tel : +44 (0) 1376 5141 14
mark.aheme@timefreq.com

tfs Time & Frequency Solutions

25 Eastways, Witham, Essex, CM8 3AL, UK
Phone +44 (0) 1376 5141 14 | Fax +44 (0) 1376 5161 16
enquiries@timefreq.com

Brandywine
communications

153 Warner Ave, Tustin, CA 92780, USA
Phone +1 714 755 1050
Info@brandywinecomm.com

Please visit our web sites at www.brandywinecomm.com or www.timefreq.com or call one of our regional offices.

Disclaimer : Brandywine & TFS are always seeking to improve our products, the information in this document only provides general indications of product capability, suitability and performance, none of which shall form any part of any contract.