

GPSDO - GPS DISCIPLINED OSCILLATOR MODULE



**GPS Referenced
Commercial Off The Shelf (COTS)
Multi Output 10 MHz Frequency Standard**



AS9100D Certificate Number : C0210021-AS3



GPSDO - GPS DISCIPLINED OSCILLATOR MODULE

Product Overview

The GPS Disciplined Oscillator Module is a small Commercial –Off-the-Shelf (COTS) GPSDO that has been designed to meet military requirements such as MIL-STD-188-164A.

At only 4.1” x 2.75” x 1” (104.0 x 70.0 x 26.0 mm) in size, the unit provides Stratum 1 performance. The GPSDO supplies three isolated, low noise precision 10 MHz frequency reference signal outputs. These outputs are accurate to 1x10⁻¹² when slaved to a timing supply from an internal GPS tracking receiver.

The frequency standard is also able to slave to an external 1PPS signal to steer and hold the internal oscillator and clock system precisely in time. Time and frequency information is maintained to a very high accuracy during by the disciplined internal oscillator even when no satellites can be tracked.

A serial data port is provided to report time, date, position, and GPS satellite health and signal strength. The GPSDO module also has dual power supply inputs and can operate off either supply input.

Optional capabilities include automatic interface to an external military GPS receiver such as the Defence Advanced GPS Receiver (DAGR), Ethernet Interface for NTP time service and SNMP status monitoring. Standard frequency output is 10 MHz, but other frequencies are also possible.

Key Feature Summary

Timing & Interfaces

- 3 Isolated Low Phase Noise 10MHz Outputs
- Internal GPS Tracking Receiver
- External 1PPS Input
- Small Footprint Designed for easy Integration
- Disciplined High Stability OCXO

Outputs

- 3 Isolated Low Phase Noise 10MHz Outputs
- Serial Time Of Day Message TOD



Also of interest may be our Miniature GPS reference oscillator module



GPSDO - GPS DISCIPLINED OSCILLATOR MODULE

Specifications



Specifications - GPSDO	
Reference Signal Inputs - 1PPS	Details
Connectors	1 x MCX Connector
Amplitude	0V to 5V - 50 Ohms
Reference Signal Inputs - GPS	
Connectors	1 x MCX Connector
Receiver Type	Satellite Signal : 12 Channels : GPS L1 1575.42 Mhz / Satellite Code : C/A code 1.023 MHz
Sensitivity	155dBm
Reference Signal Inputs - HQ	
Optional Have Quick Input Ref	1 x MCX Connector : per ICD-GPS-060
Accuracy Details	
Time Accuracy - GPS	< 30ns
Time Accuracy - 1 PPS	< 30ns
Holdover	< 20µs in 24 hrs
Power Supply Details	
Connectors	2 x Headers, diode OR'd together
Power	12V DC or 15V DC Supply (Specify at order point) Warm up consumption : 15 Watts Steady State : 5 Watts
Outputs	
1 PPS	1 x MCX Connector : 0 - 5V DC into 50 Ohms - Complies with ICD-GPS-060
10 MHz	3 x MCX Connectors : 2 off Outputs at 7dBm +/- 2dBm 1 off Output at 15dBm +/- 2dBm (requires + 15V supply)
I/O Connector	
Interface Signals	Power A (12 or 15V DC) Power B (12 or 15V DC) Alarm Out 1 PPS Input Reset Force Holdover / HQ input RS232 Locked
Environmental	
Temperature	Operational : -20°C + 70°C / Storage -40°C to + 85°C.
Humidity	95 % non condensing
Altitude	Operational to 10,000 ft - transit not operational to 50,000 ft
Physical	104mm x 70mm x 26mm
Compliance	CE Approved - EMC Emissions to EN55022 as EN55024 - FCC Part 15B, Class A

Phase Noise / Short Term Stability (10MHz)	
SSB Phase Noise	dBc/Hz
1 Hz	-90
10 Hz	-120
100 Hz	-145
1 KHz	-151
10 KHz	-153
100 KHz	-155
STS (Allan Variance) (after 24hrs)	
1 Sec	< 8.0 x 10-12
10 Sec	< 1.0 x 10-11
100 Sec	< 1.5 x 10-11
1000 Sec	< 1.5 x 10-11

Satisfied customers include..

ABB Singapore

Airbus Defence & Space

ASM Technologies Ltd

Atkins

Babcock International

BAE Systems

BBC

Carillion Rail

CMC Engineering Malaysia

EDF Energy

Finmeccanica, UK

Indian Navy

Jakarta Metro

Leonardo Electronics Defence And Security

London Stock Exchange

London Underground

MBDA Ltd

MTRC Hong Kong

National Air Traffic Services

NEC

Network Rail National

Northrop Grumman Park Air Systems Ltd

Qinetiq Ltd

Raytheon Systems Ltd

Rockwell Automation

SBS Transit Singapore

Siemens Rail

Siemens Rail Automation Holdings Ltd.

Singapore Stock Exchange

St Electronics Singapore

Telent Technology Services Limited

Teligent

Thales UK

Transport For London

Viacom



Asia, China, India, Japan

Mr Neil Pitman
Director of Sales - Asia
China, India, Japan

+44 (0) 1376 5141 14 Phone
neil.pitman@timefreq.com

Europe, Middle East, Africa, Australia

Mr David Wright
Director of Sales, Europe, Middle East,
Africa, Australia

Tel : +44 (0) 1694 722891
dwright@timefreq.com

United Kingdom

Mr Mark Aheme
Director of Sales, UK

Tel : +44 (0) 1376 5141 14
mark.aheme@timefreq.com

tfs Time & Frequency Solutions

25 Eastways, Witham, Essex, CM8 3AL, UK
Phone +44 (0) 1376 5141 14 | Fax +44 (0) 1376 5161 16
enquiries@timefreq.com

Brandywine
communications

153 Warner Ave, Tustin, CA 92780, USA
Phone +1 714 755 1050
Info@brandywinecomm.com

Please visit our web sites at www.brandywinecomm.com or www.timefreq.com or call one of our regional offices.

Disclaimer : Brandywine & TFS are always seeking to improve our products, the information in this document only provides general indications of product capability, suitability and performance, none of which shall form any part of any contract.