

M355

LED Digital Time Display

4 or 6 Digit

Suitable for any interior application where clearly presented time or date information is required. Can be used in conjunction with any time and frequency equipment with the required output interface.

M355 Product Options



N.B. images are for illustration purposes only

Feature	M355
No. of Digits	4 (HH:MM) / 6 (HH:MM:SS)
Digit Size (mm)	60 / 100
Digit Type	7 Segment
Digit Colour	Red / Yellow
Input Signal	NTP / Serial
Power	AC / PoE+
Front	Acrylic
Application	Indoor
Mounting	Ceiling / Wall

Features

- High-intensity LED digits
- Excellent readability
- Suitable for interior applications

Applications

The range of product options available can create suitable configurations for diverse indoor applications.

Rail Applications

The M355 is perfect for metro rail applications. The display supports proprietary industry-specific serial message inputs which is essential in some rail applications..

Network Time Display

The M355 becomes a Network Time Display if Network Time Protocol (NTP) input signal option is selected. The display automatically acquires accurate time at any location where a network connection is available. Alternatively, the display can be manually configured to run autonomously. NTP displays may be supplied to use Power over Ethernet (PoE) if required (as opposed to the standard AC).



M355 Specifications

General

Display Digit Colour: Red, Yellow
 Standard Case Colour: Black
 Power: 90-264V AC 48-62Hz or PoE+

Network Time Display

Interface Standards: NTPv3 (RFC 1305)
 Connection: External RJ45 (10/100BaseT)
 Configuration: Via Web Browser available through RJ45 port
 Parameters include IP address, Subnet Mask, and Gateway Address
 Configuration details stored in non-volatile memory.

Serial Time Display

Data Protocol: Configurable Serial port option for legacy input message support
 Interface Standards: RS232 / RS422 / RS485
 Connection: Via RJ45 (AC option only)
 Configuration: Via Web Browser available through RJ45 port
 Parameters include IP address, Subnet Mask, and Gateway Address
 Configuration details stored in non-volatile memory.

Environmental (Operation & Storage)

Temperature: 0°C to +40°C.
 Humidity: Up to 95% RH (non condensing)

Physical Dimensions & Viewing Distances

Size	Display Information	Digit Height (mm)	Width (mm)	Height (mm)	Depth (mm)	Weight (kg)	Max Viewing Distance (m)
4 Digit	HH:MM	60	332	81	76	1.6	25
	HH:MM	100	433	136	76	2.2	50
6 Digit	HH:MM:SS	60	372	81	76	1.8	25
	HH:MM:SS	100	655	136	76	2.5	50

As we are always seeking to improve our products, the information in this document only provides general indications of product capability, suitability and performance, none of which shall form any part of any contract.